CRAFT SOURCE

How to Use

- Print design (Do not Mirror) If using print and cut make sure you are printing with registration marks on.
- Send to your vinyl cutting machine or trim with scissors around your design. If you do not cut around the design the white area's will show on garment.
- Weed the design and apply TTD EASY MASK to the design. This is your Heat Transfer Tape.
- Remove the backing sheet and you are ready to press.

Troubleshooting

Q:My design will not transfer to the mask?

A:This is a sign your machine cut to deep, if you cut with scissors simply turn the design face down and use a weeding tool to hook the backing paper in the corner to begin the release and peel away the backing. For intricate print and cut designs you can work slowly and patiently to release the pieces with a weeding tool. We always suggest test cutting your materials as every machine cuts differently due to quality and life span.

Q:My ink is coming off with the mask after I press it onto the garment?

A:This product is a Cold peel. You need to let the design cool all the way before removing the TTD Easy Mask. If this does not solve the ink transferring I would double check the temperature, pressure and time for this product to make sure the settings are correct.

Updated on: 09/07/20



Application Instructions

Home Iron:

Due to the even distribution of heat needed with this product we do not recommend this method of application.

Easy Press:

Due to the even distribution of heat needed with this product we do not recommend this method of application.

Heat Press:

- Cover design with Teflon Sheet
- Pre-heat Garment for 2-3 seconds
- Apply Design at 350°F/176°C
- Use Medium Pressure for 30 seconds
- Peel Mask Cold

Tips: Do not mirror. Use TTD Easy Mask to transfer off of backing sheet. Do not pre wash garments, and wait 24 hours before first wash. Machine wash cold, inside out with mild detergent. Dry on normal dryer setting. Do not dry clean.



HEAT TRANSFER VINYL CUT SETTINGS FOR CAMEO

Vinyl Type	Blade	Speed	Force
Siser: EasyWeed, Electric, Stretch, Extra, Glow in the dark, and EW Adhesive	2	8	4
Siser Glitter	4	8	30
Siser Twinkle	3	8	12
Siser Sparkle	2	8	12
Siser Holographic & Metal	3	5	14
Siser Brick	10	5	33
Siser StripFlock Pro	4	5	12
Siser Reflective	3	8	6
StarCraft SoftFlex	2	8	8
StarCraft InkJet Printable: Dark Materials	2	8	6
Printed Pattern HTV Do not mirror*	3	8	6
Easy Subli	3	5	8



HEAT TRANSFER VINYL CUT SETTINGS FOR CRICUT EXPLORE

Vinyl Type	Dial	Pressure Custom	Pressure
Siser: EasyWeed, Electric, Stretch, Extra, Glow in the dark, and EW Adhesive	Iron on	-	Default
Siser Glitter	Cardstock	ı	Default
Siser Twinkle	Iron on+	-	Default
Siser Sparkle	Iron on+	-	Default
Siser Holographic & Metal	Iron on+	-	Default
Siser Brick	Iron on+	-	Default
Siser StripFlock Pro	Iron on+	1	Default
Siser Reflective	Iron on+	-	Default
StarCraft SoftFlex	Iron on	-	Default
StarCraft InkJet Printable: Dark Materials	Iron on	-	Default
Printed Pattern HTV	Iron on	-	Default
Easy Subli	Iron on+	-	Default



HEAT TRANSFER VINYL CUT SETTINGS FOR CRICUT MAKER

Vinyl Type	Material	Pressure Custom	Pressure
Siser: EasyWeed, Electric,	Everyday	-	Default
Stretch, Extra, Glow in the	Iron-On		
dark, and EW Adhesive			
Siser Glitter	Glitter	_	Default
Sisci dilitti	Iron-On	•	Delauit
Siser Twinkle	Glitter	_	Less
	Iron-On	VII. VII.	Less
Siser Sparkle	Everyday	-	More
	Iron-On		111010
Siser Holographic & Metal	4000 MA 100 MA 1	_	Default
	Heat Transfer		2014410
Siser Brick	Flocked	_	More
	Iron-On		1,1010
Siser StripFlock Pro	Flocked	_	Default
	Iron-On		
Siser Reflective	Everyday	_	More
	Iron-On		
StarCraft SoftFlex	Everyday	_	Default
	Iron-On		56 500 5000 6
StarCraft InkJet Printable:	Printable	_	Default
Dark Materials	Iron-On-Dark		
Printed Pattern HTV	Patterned	-	Less
	Iron-On		LCSS
Easy Subli	custom	118	Default