CRAFT SOURCE

How to Use

- Place pattern side up on your mat. (DO NOT MIRROR DESIGN)
- Cut design, only through the HTV and not all the way through the backing.
- Weed out your design.
- Apply the TTD Easy Mask to the design with a squeegee creating a good bond.
- Turn it over and remove the backing sheet. Squeegee on the back as well if there is transfer resistance.
- Once the design is on the mask you are ready to press.

Troubleshooting

Q: I mirrored my design can I still use it?

A: Unfortunately no you cannot.

Q: I did not purchase the TTD Easy Mask, can I still use it?


A: If you have a clear carrier sheet from a regular piece of HTV you can use that.

Q: My TTD Mask will not pick up the design?

A: This can be a sign that the product was cut to deep. If you use a weeding tool to release the edges to get it started it will help. You can also use a squeegee to press and guide the backing away little by little.

Q: If I have bubbles or wrinkles in my transferred design will it press out?

A: Most of the time this does resolve in the press. We suggest working as many of them as out before pressing if possible.





Application Instructions

Home Iron:

- Cover design with Teflon Sheet, use flat hard surface. (Ironing board not recommended)
- Pre-heat Garment for 2-3 seconds
- Set Dial on Cotton
- Use Body weight with Full Pressure for 15 seconds on each section. Do not slide Iron.
- Peel carrier hot or cold

Easy Press:

- Cover design with Teflon Sheet
- Pre-heat Garment for 2-3 seconds
- Apply Design at 335°F/168°C
- Use Body weight with Medium Pressure for 15 seconds
- · Peel carrier hot or cold

Heat Press:

- · Cover design with Teflon Sheet
- Pre-heat Garment for 2-3 seconds
- Apply Design at 305°F/151°C
- Use Medium Pressure for 15 seconds
- Peel carrier hot or cold

Tips: Do not mirror, this product only works with the TTD Easy Mask. Pressure is key to a good press. Do not pre wash garments, and wait 24 hours before first wash. Machine wash cold, inside out with mild detergent. Dry on normal dryer setting. Do not dry clean.



HEAT TRANSFER VINYL CUT SETTINGS FOR CAMEO

Vinyl Type	Blade	Speed	Force
Siser: EasyWeed, Electric, Stretch, Extra, Glow in the dark, and EW Adhesive	2	8	4
Siser Glitter	4	8	30
Siser Twinkle	3	8	12
Siser Sparkle	2	8	12
Siser Holographic & Metal	3	5	14
Siser Brick	10	5	33
Siser StripFlock Pro	4	5	12
Siser Reflective	3	8	6
StarCraft SoftFlex	2	8	8
StarCraft InkJet Printable: Dark Materials	2	8	6
Printed Pattern HTV Do not mirror*	3	8	6
Easy Subli	3	5	8



HEAT TRANSFER VINYL CUT SETTINGS FOR CRICUT EXPLORE

Vinyl Type	Dial	Pressure Custom	Pressure
Siser: EasyWeed, Electric, Stretch, Extra, Glow in the dark, and EW Adhesive	Iron on	_	Default
Siser Glitter	Cardstock	-	Default
Siser Twinkle	Iron on+	-	Default
Siser Sparkle	Iron on+	-	Default
Siser Holographic & Metal	Iron on+	-	Default
Siser Brick	Iron on+	-	Default
Siser StripFlock Pro	Iron on+	1	Default
Siser Reflective	Iron on+	-	Default
StarCraft SoftFlex	Iron on	1	Default
StarCraft InkJet Printable: Dark Materials	Iron on	-	Default
Printed Pattern HTV	Iron on	-	Default
Easy Subli	Iron on+	1=	Default



HEAT TRANSFER VINYL CUT SETTINGS FOR CRICUT MAKER

Vinyl Type	Material	Pressure Custom	Pressure
Siser: EasyWeed, Electric,	Everyday	-	Default
Stretch, Extra, Glow in the	Iron-On	137 - 110	Boraure
dark, and EW Adhesive			
Siser Glitter	Glitter	_	Default
Sisci Gilllei	Iron-On		Delauit
Siser Twinkle	Glitter	_	Less
	Iron-On		Less
Siser Sparkle	Everyday	-	More
	Iron-On		1010
Siser Holographic & Metal	Holographic	_	Default
	Heat Transfer		Beraute
Siser Brick	Flocked	-	More
	Iron-On		1,1010
Siser StripFlock Pro	Flocked	-	Default
	Iron-On		2 0100010
Siser Reflective	Everyday	_	More
	Iron-On		1.1010
StarCraft SoftFlex	Everyday	_	Default
	Iron-On		
StarCraft InkJet Printable:	Printable	_	Default
Dark Materials	Iron-On-Dark	· -	Detaut
Printed Pattern HTV	Patterned	I	Less
	Iron-On		LCSS
Easy Subli	custom	118	Default